



# Advant

Ultra High Performance Full Synthetic European

## Features & Benefits

- Robust engine performance
- Exceptional wear and sludge protection
- Excellent piston cleanliness

## Specifications

✓ Meets Requirements ◆ Recommend for

Specification/Claim	5W-30	5W-40
API SN/CF	-	✓
API SL/CF	✓	✓
ACEA A3/B3	✓	✓
ACEA A3/B4	✓	✓
ACEA A5/B5	✓	-
JASO MA-2	◆	◆
MB 226.5	◆	◆
MB 229.3	◆	◆
MB 229.5	◆	-
VW 502.00/505.00	◆	◆
RN 0710/RN 0700	◆	◆
Porsche A40	-	◆

## Typical Results

Methods	5W-30	5W-40
DENSITY @ 15°C (D4052) (kg/L)	0.85	0.85
VISCOSITY (D445) cSt @ 40 °C	68.8	84.6
cSt @ 100 °C	11.8	14.1
VISCOSITY INDEX (D2270)	168	173
POUR POINT (°C) (D97)	-36	-36
FLASH POINT (°C) (D93)	211	214
TOTAL BASE NUMBER (D2896) (mg KOH/g)	10	10
COLD CRANK (D5293) cP@-30(°C)	5365	6389

## Sizes & Order Codes

Sizes	5W-30	5W-40
946 mL / 1 US Qt.	F0096006	F0000206
5 L / 1.32 US Gal	-	F0000230
60 L / 15.8 US Gal	F0096045	F0000245
205 L / 54.2 US Gal	F0096050	F0000250
1000 L / 264 US Gal Bulk Tote	F0096001	F0000201



**ADVANT** 100% synthetic passenger car motor oil offers the ultimate lubricant protection for European gasoline and diesel-powered automobiles.

**ADVANT** is no ordinary motor oil, it is a sophisticated formula of pure and stable base stocks coupled with the latest in additive technology. This formulation will deliver the performance and protection your engine demands.

**ADVANT** was formulated to keep your engine as close as possible to factory cleanliness. The tighter the clearances in your engine the cleaner you need to run, even a small deposit can make a major difference in performance.

**ADVANT** has excellent cold-start protection circulating quickly to create a protective film for vital engine components. When used in extreme high temperatures this protection reduces wear, resists oxidation and retains viscosity stability to extend engine service life.

*\*Although long life is a feature of the stability of synthetic oils, the engine manufacturers' oil drain intervals should always be respected.*



[www.irvingoil.com/lubricants](http://www.irvingoil.com/lubricants)  
1.800.574.5823