

Bio Form Oil 10

Form wetting and releasing agent

Features & benefits

- Biodegradable
- Reduces wear and extends form life
- Protects wood, metal and plastic forms
- Good corrosion inhibitors
- Low pour point

Typical results

Test Method	Bio Form Oil 10
VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	9.6 2.6
VISCOSITY INDEX (D2270)	107
ASTM COLOUR (D1500)	1.0
DENSITY @ 15°C (D4052), kg/L	0.83
POUR POINT (D97), °C	-42
FLASH POINT (D93), °C	178

Sizes & order codes

Size	Bio Form Oil 10
205 L (54.2 US gal)	F0120150
1000 L (264 US gal)	F0120160
Bulk	B0120101



Bio Form Oil 10 is biodegradable. This oil has been formulated to act as an excellent lubricant while ensuring very little danger to the environment.

Bio Form Oil 10 is suitable for molds made from wood, aluminum, steel and plastic.



Always consult your owner's manual for verification of fluid type and grade!

Supporting data available to demonstrate acceptable performance. Check with Sales Associate for the latest product approvals.

Please note these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to August 6, 2024.

www.irvingoil.com/lubricants 1.800.574.5823