

# Form Oil

## Form wetting and releasing agent

### Features & benefits

- Easy to use—can be painted or sprayed on
- Low pour point for year-round use
- Non-staining formula
- Effective
- Versatile – can be used as a general protective coating
- Leave a smooth surface

### Typical results

Test Method	Form Oil
VISCOSITY (D445) cSt @ 40°C	6.2
ASTM COLOUR (D1500)	2.0
DENSITY @ 15°C (D4052), kg/L	0.85
POUR POINT (D97), °C	-33
FLASH POINT (D93), °C	65

### Sizes & order codes

Size	Form Oil
18.9 L (5 US gal)	F0084440
205 L (54.2 US gal)	F0003850
1000 L (264 US gal)	F0003860
Bulk	B0003801



**Form Oil** is a blend of quality paraffinic base oil and petroleum distillate and is used as a form-release agent with a rust-preventive coating.

**Form Oil** is coated on to concrete form-work prior to being filled with concrete.

**Form Oil's** viscosity allows it to be sprayed or brushed on and the light colour won't stain the concrete. A fatty material added to the formula reacts with the alkalis in the cement to form a barrier between the form and the cement that helps them to separate easily and leaves the concrete with a smooth surface. This also protects wood forms from tearing and reduces the maintenance time needed to remove dried concrete from the form surface.

**Form Oil** as a coating helps prevent steel forms and machinery from rusting and prevents wood forms from absorbing water and rotting.



**Always consult your owner's manual for verification of fluid type and grade!**

Supporting data available to demonstrate acceptable performance. Check with Sales Associate for the latest product approvals.

Please note these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to November 7, 2024.

[www.irvingoil.com/lubricants](http://www.irvingoil.com/lubricants) 1.800.574.5823