



Global Antifreeze/Coolant

Pre-mixed 50/50

Features & benefits

- Newer vehicle makes & models
- Protects all coolant system metals, including aluminum
- Ready to use 50/50 pre-mix for ultimate convenience
- Extended service life for reduced maintenance
- Provides up to 250,000 km or 5 years of protection ¹
- Free of borate, nitrite, amine, phosphate, silicate and 2-Ethylhexanoic Acid



Global Antifreeze/Coolant is a premium Organic Acid Technology (OAT) long-life antifreeze for the cooling systems of all makes and models of foreign and domestic passenger vehicles, light-duty trucks, and SUVs. This product uses exclusive corrosion inhibitors to protect all coolant system metals against rust, corrosion, and pitting caused by cavitation.

Global Antifreeze/Coolant ensures excellent protection against temperature extremes, preventing freeze-up and boil-over when used in accordance with OEM and product manufacturer's guidelines.

Global Antifreeze/Coolant is formulated with a special yellow dye for easy identification. The superior performance and stability of the maximum life corrosion inhibitors allow them to keep working well beyond the lifetime of traditional products.

Global Antifreeze/Coolant protects up to 250,000 km (150,000 miles) or five years when added to the coolant system after a complete drain, flush, and fill.

Global Antifreeze/Coolant is a 50/50 blend with de-mineralized water.

Sizes & order codes

Size	Global Antifreeze/Coolant
3.78L (1 US gal)	F0075126
205 L (54.2 US gal)	F0075150
1000 L (264 US gal)	F0075160

Specifications

✓ Meets requirements

Specification	Global Antifreeze/Coolant
ASTM D3306	✓
Japanese Industrial Standard JIS K 2234	✓

Typical results

Test Method	Global Antifreeze/Coolant
COLOUR	Yellow
SPECIFIC GRAVITY @ 15.6°C / 60°F (D1122)	1.07 - 1.09
FREEZE POINT (D1177), °C / °F	-37/-34
RESERVE ALKALINITY (D1121), mL	1.8 min
pH (D1287)	7.5 - 8.5
FOAM VOLUME (D1881), mL	150 max
FOAM BREAK TIME (D1881), sec	5 max
ETHYLENE GLYCOL CONTENT, wt. %	47 min
INHIBITORS & WATER CONTENT, wt. %	54 max
CHLORIDE (D3634), ppm	25 max

¹ When added to the coolant system after a complete drain, flush and fill.

Always consult your owner's manual for verification of fluid type and grade!

Supporting data available to demonstrate acceptable performance. Check with Sales Associate for the latest product approvals.

Please note these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to January 16, 2025.

www.irvingoil.com/lubricants 1.800.574.5823